



SAFETY DATA SHEET

PRIVATE LABEL 25% SOLIDS METALLISED FLOOR POLISH PLF145 SPD997

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PRIVATE LABEL 25% SOLIDS METALLISED FLOOR POLISH PLF145 SPD997

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent

1.3. Details of the supplier of the safety data sheet

Supplier STAPLES CHEMICALS
NEVILLE HOUSE
BEAUMONT ROAD,
BANBURY,
OXON OX16 1RB
01295 251721
01295 269561
sales@cleenol.co.uk

1.4. Emergency telephone number

Emergency telephone Emergency contact number 01295 251721 (9am to 5pm Monday to Friday excluding bank holidays). Ask for Technical Department quoting the product name. Outside of these hours please contact your doctor or local hospital accident and emergency department or the NHS enquiry service (dial 111) quoting product name and present this MSDS advising them that the product is registered with the National Poisons Information Service

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

Precautionary statements P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.

Supplementary precautionary statements P102 Keep out of reach of children.

2.3. Other hazards

Other Hazards None

PRIVATE LABEL 25% SOLIDS METALLISED FLOOR POLISH PLF145 SPD997

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACRYLIC POLYMER	10-30%
CAS number: —	
Classification Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) R 52/53.
WAX	1-5%
CAS number: —	
Classification Eye Irrit. 2 - H319	Classification (67/548/EEC or 1999/45/EC) Xi;R36.

The Full Text for all R-Phrases and Hazard S t atements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Ingestion	Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause respiratory irritation.
Ingestion	May cause discomfort if swallowed.
Skin contact	May cause skin irritation.
Eye contact	May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments	Seek medical attention if irritation or symptoms persist. Symptomatic treatment
----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Burning may produce irritating, toxic and obnoxious fumes. Oxides of Carbon, Nitrogen and Sulphur.
-------------------------	---

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet
-----------------------------	--

PRIVATE LABEL 25% SOLIDS METALLISED FLOOR POLISH PLF145 SPD997

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections See section 3,8 & 13 for further information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SHELF LIFE OF DILUTION

12 MONTHS

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment



Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Use barrier creams to prevent skin contact

Hygiene measures

Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin.

Respiratory protection

Not relevant

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Milky.

PRIVATE LABEL 25% SOLIDS METALLISED FLOOR POLISH PLF145 SPD997

Odour	Characteristic.
pH	8-10
Initial boiling point and range	100@ °C @ 760 mm Hg
Relative density	1.032@ @ 20c°C

9.2. Other information

Other information	None.
-------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
-----------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.
------------------------------------	-------------

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
---------------------	---

10.5. Incompatible materials

Materials to avoid	None known.
--------------------	-------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂).
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Ingestion	May cause discomfort if swallowed.
Skin contact	Skin irritation should not occur when used as recommended.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.

SECTION 12: Ecological Information

Ecotoxicity	Not regarded as dangerous for the environment
-------------	---

12.1. Toxicity

Toxicity	The product is not believed to present a hazard due to its physical nature.
----------	---

12.2. Persistence and degradability

Persistence and degradability	The product is biodegradable.
-------------------------------	-------------------------------

12.3. Bioaccumulative potential

Bioaccumulative potential	Not known.
---------------------------	------------

12.4. Mobility in soil

Mobility	The product is soluble in water.
----------	----------------------------------

PRIVATE LABEL 25% SOLIDS METALLISED FLOOR POLISH PLF145 SPD997

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

PRIVATE LABEL 25% SOLIDS METALLISED FLOOR POLISH PLF145 SPD997

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG 228.
Approved Classification and Labelling Guide (Sixth edition) L131.
Safety Data Sheets for Substances and Preparations

15.2. Chemical safety assessment

A chemical safety assessment has been carried out

SECTION 16: Other information

Revision date	13/10/2017
Revision	10
Supersedes date	29/09/2017
SDS number	PLF145
Risk phrases in full	Not classified. R36 Irritating to eyes. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Hazard statements in full	H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.